

# CELLULOSE

with TACK



- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD CELLULOSE FIBER MULCH
- REDUCES FRICTION IN HOSE, INCREASES SLURRY SHOOTING DISTANCE, CONTROLS EROSION WITHOUT HAVING TO CURE
- HOLDS MORE WATER – IMPROVING TURF ESTABLISHMENT

## DIRECTIONS FOR USE

WHILE FILLING HYDRAULIC SEEDER WITH WATER ADD SEED, CELLULOSE FIBER WITH TACK AND FERTILIZER. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.



## PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
ORGANIC CONTENT	90.0% +-3
pH RANGE	7.0 +-2
TACKING AGENT III	3.0% MIN
WATER HOLDING CAPACITY	1200% MIN

## TYPICAL APPLICATION RATE

3 TO 1 SLOPE	2000 LBS / ACRE
STRAW MULCH BINDING	500 LBS / ACRE

## PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER PALLET

**Distributed by:**

