BLEND
with TACK

- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD & PAPER FIBER MULCH
- REDUCES FRICTION IN HOSE, INCREASES SLURRY SHOOTING DISTANCE AND CONTROLS EROSION WITHOUT HAVING TO CURE
- IMPROVED WATER HOLDING CAPACITY, INCREASING COVERAGE WHILE REDUCING EROSION

DIRECTIONS FOR USE

AFTER FILLING HYDRAULIC SEEDER 1/3 FULL WITH WATER ADD SEED, BLEND FIBER MULCH with TACK AND FERTILIZER AS YOU CONTINUE TO FILL TANK. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.

PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
WOOD FIBER	70% MIN
CELLULOSE FIBER	30% MAX
ORGANIC CONTENT	96.0% +-1
TACKIFIER	3.0% +-.2
ASH CONTENT	1.0% +-1
pH RANGE	4.8 +-2
WATER HOLDING CAPACITY	1200% MIN

TYPICAL APPLICATION RATE

3 TO 1 SLOPE	2000 LBS / AC

PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER PALLET

Distributed by: