

WOOD WITH TACK



- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD MULCH
- REDUCES FRICTION IN HOSE, INCREASES SLURRY SHOOTING DISTANCE AND UNIVERSITY TESTED TO CONTROL EROSION WITHOUT HAVING TO CURE
- DYED A DARK GREEN COLOR FOR EASY METERING

DIRECTIONS FOR USE

WHILE FILLING HYDRAULIC SEEDER 1/3 FULL WITH WATER ADD SEED, WOOD w/TACK MULCH AND FERTILIZER TO TANK. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.



PHYSICAL PROPERTIES

| | |
|------------------------|-----------|
| MOISTURE CONTENT | 12% +-3 |
| ORGANIC CONTENT | 96.2% +-4 |
| ASH CONTENT | .8% +-4 |
| TACKIFIER | 3.0% MIN |
| pH RANGE | 4.8 +-2 |
| WATER HOLDING CAPACITY | 1350% MIN |

TYPICAL APPLICATION RATE

2.5 TO 1 SLOPE 2000 LBS / AC

PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER PALLET

Distributed by:

